


# JARVIS 10" Meeting Room Commercial Android Tablet



**Capacitive Touch**



**Optional POE**



**Durable Built to Last**

## Overview

Glory Star room display tablet is designed in a 1.7cm sleek housing with embedded LED lights in green, red and yellow. The tablet is designed for room management, resource management and building automations. It is based on a license free Android OS platform, Glory Star provides open API and technical support for developers. It includes a lockdown software that allows the device to turn on and go automatically to the meeting room/ scheduling applications

Available in 10" widescreen with high performance CPU's and IPS capacitive touchscreens

Choice of Wi-Fi / Ethernet

Optimize deployments with cloud-based configuration, monitoring and scheduling

Modern design with flexible mounting portrait, landscape and table-top orientation

	Model	JAR101 Part#CT128MR/PE
Screen Size	Size	10"
Panel Info	Resolution	1280x 800
	Brightness	450cdm2
	Contrast	800:1
	Aspect Ratio	16:10
	Active Display Area	135.6 ( H )x 216.96 ( W )mm
	Viewing Angle	H170°/ V170°
Touch Data	Touch Tech	5 point cap touch (reflective glass)
Hardware & OS	CPU	RK3128 Cortex - A7, Quad core 1.2GHz
	RAM	1GB DDR3
	ROM	8GB eMMC Flash
	OS	Android 7.1
Software	STAROS	· Kiosk lockdown · App Lockdown · Set timer to turn device on and off · Hide control buttons
	STARCONTROL	· Manage device remotely · Control power on/off · Upload video to device · Manage apps remotely
	STARTOOL	Tool for developers to control device and Open API
Video/ Image	Video Format	H.265, VP8, RV, WMV, AVS, H.263, MPEG4, Up to 4K x 2K decoding, HTML5, Flash 10
	Audio Format	MP3/ WMA/ AAC etc.
	Image Format	JPEG, BMP, PNG
Audio	Speaker	1W x2
Communciation	Bluetooth	BT 4.0
	Camera	2 Megapixel with fixed focus
WIFI	WIFI	802.11 b/g/n
	Ethernet	10/100 LAN with POE
General	Color	Black
	Chasis	Plastic
	I/O	RJ45 x 1; USB x 1; SD slot x 1; Micro-USB x 1; 3.5mm audio x 1; Recover x 1
	POE	Optional Extra I/O for JAR101, IEEE802.3af standard
	Included in Box	Meeting Room Tablet, Power Adaptor, Power Cable
	Sensors	G- sensor
	Consumption	11W
	Power Input	12V 2A
	Operating Environment	Operating: 32°F to 104°F (0°C to 40°C); Storage: -4°F to 122°F (-20°C to 50°C) Operating: 20%-80%; Storage: 10%-95%
	Language	Multi language
Mounting	VESA	VESA 75
	Certification	CE, FCC, ROHS, UKCA
Dimensions	Dimensions ( LxWXH)	251.88 × 171.96 x 35 mm
	Weight	665g
	Box size / each pc (LxWXH)	385 x 65x222 mm
	Master Box size ( LxWXH)	470×400×355 mm
	Master Box Weight	13.4Kg
	Pieces/ Carton	10 PCS

## Mounting Options

Shelf Mount	FIX-014 (Foldable Mount with Magnet at one side )
	FIX-001+ FIX-017 (Shelf Clamp)
Wall Mount	WMO15012S
Desk Mount	FIX-028 ( Adjustable Desk Mount)

## Peripheral Options

Option	Details
1D Barcode Newland Plastic Housing	NEBA1701 Part#EM1365
2D Barcode Newland Plastic Housing	NEBA1702 Part# EM3396

## CONTACT US

United States	Hong Kong	ShenZhen
1440 N. Harbor Blvd Suite 900 Fullerton, CA 92835, USA 626 228 5927	Flat D, 5/F, Excelsior Building, 364 Nathan Road, Kowloon, Hong Kong 852 23762803	Bldg 9, 4/F Zhong Yuntai Technology Industrial Park, Tangtou No.1 Road, Shiyan Street, Baoan, ShenZhen, PRC 86 755 2600 1808

To find out more about our extensive range of Glory Star solutions, go to [www.glorystargroup.com](http://www.glorystargroup.com), or call the office nearest you. For more information, please contact us at [sales@glorystargroup.com](mailto:sales@glorystargroup.com). Glory Star reserves the right to change or update, without notice, any information contained herein; to change, without notice, the design, construction, materials, processing or specifications of any products; and to discontinue or limit production or distribution of any products. Glory Star, the Glory Star logo, STAR CONTROL and STAROS are either trademarks or registered trademarks of Glory Star Group Limited. All other trademarks are the property of their respective owners.