

VEGA X Gen 2 Access Control











Identify & track via RFID



API third party integration



Micro USB Updates

Overview

Glory Star's Vega X is an IP65 waterproof outdoor access control device that supports SIP with IP calling. Running on an Android operating system, it offers third-party software developers and system integrators the ability to develop their software and services on top of Vega X and VegaOS. Private label services are also available, in addition to selling and supporting Vega X. This device is specifically designed for gate entrances, commercial and residential building entrances. Glory Star's open API combined with the Android platform has created a low barrier to entry, resulting in a high ROI for software developers and system integrators.

Echo-Canceling

Proximity Sensor

RFID

Reduce Installation cost

Ambient Sensor

POE

IP65 Waterproof & Anti-Glare tempered glass

	Model	VOD073 Part# CT568	
Screen Size	Size	7"	
Panel Info	Resolution	1280 x 800	
	Brightness	400cdm2	
	Contrast	800:1	
	Aspect Ratio	16:10	
	Active Display Area	149.76 x 93.60mm	
	Viewing Angle	88°/88°/88°	
	Response time	40ms	
Touch Data	Touch Tech	10-point waterproof touch, high temperature ceramic ink + AG + AF	
	Hardness Of Surface	6Н	
	Touch method	Finger touch 、Dedicated metal pen	
	Transparency	>50%	
	Touch Glass Thickness	2.72mm	
	Response time	TBD	
Hardware & OS	CPU	Quad Core Cortex A55 up to 2.0GHz	
riaraware a 05		TTOPSNPU	
	RAM	4GB DDR4	
	ROM	32GB eMMC Flash	
	OS	Android 12	
Software	VEGA OS	Smart Intercom System	
		App - Video Calling - Entry Modes (QR,Pin,RFID) - Manage Contacts - Virtual Access	
		Web Portal - All of the App control - Firmware update - Export Access Log - Set SIP server - Set Idle Time - Register RFID Card - Set NTP Server - Set Home Screen - Set Front Desk-Export Contact List - Set Relay - Customize Building Name - Set Light Strip Color	
	STAROS	License Free Kiosk Lockdown App Included	
	STAR CONTROL	Star Control Remote Device Monitoring Free 3 months Trial	
	STARTOOL	Tool for developers to control device and Open API	
Video/ Image	Video Format	MOV、FLV、MP4、MKV、MPG、VOB、AVI、WMV、etc.	
	Audio Format	WMA, WAV,AAC, FLAC, MID, APE, MP2, LRC, M4A, MP1, MP3, etc.	
Audio	Image Format	JPG、BMP、PNG、GIF、etc.	
Audio	Speaker Camera	200W HDR Camera	
Communication	Bluetooth	BT 5.0	
WIFI	WIFI	802.11 a/b/g/n/ac 2.4GHz + 5GHz	
VVII 1	Ethernet	10/100	
RFID	Frequency Range	125 kHz (LF) / 13.56 MHz (HF)	
10112	Reading distance	The EM4100 reads at a distance of >2.5cm	
		Mifare s50 S70, Desfire, FM1208 card reading distance >2.5cm	
		China's second-generation ID card 2.5cm	
General	Color	Black	
33.014.	Chassis	Plastic	
	1/0	INPUT x 2, Wiegand x 1, RS485 x 1, Relay x 2	
	POE	IEEE802.3af standard	
	Included in Box	Tablet	
	Sensors	Proximity Sensor, Ambient Sensor	
	Consumption	13W	
	Power Input	Either 12V DC or POE	
	Operating Environment	Working Temperature: 0-45 degree celsius	
	Language	Multi Language	
Mounting	VESA	N/A	
Dimensions	Dimensions (LxWXH)	262.51 x 126.51 x 31.9mm	
	Weight	0.9Kg	
	Box size / each pc	405 x 208 x 127 mm	
	(LxWXH) Master Box	440 × 420 × 405	
	size (LXWXH)		
	Master Box Weight Pieces/ Carton	8.4Kg (without bracket)	
	Pieces/ Carton	6pcs	

CONTACT US

United States	Hong Kong	ShenZhen
101 Hudson St., 21st Floor Jersey City, NJ 07302 USA 626 228 5927	Flat D, 5/F, Excelsior Building, 364 Nathan Road, Kowloon, Hong Kong 852 23762803	Bldg. 9, 4/F Zhong Yuntai Technology Industrial Park, Tangtou No.1 Road, Shiyan Street, Baoan, ShenZhen, PRC 86 755 2600 1808

To find out more about our extensive range of Glory Star solutions, go to www.glorystargroup.com, or call the office nearest you. For more information, please contact us at sales@glorystargroup.com. Glory Star reserves the right to change or update, without notice, any information contained herein; to change, without notice, the design, construction, materials, processing or specifications of any products; and to discontinue or limit production or distribution of any products. Glory Star, the Glory Star logo, STAR CONTROL and STAROS are either trademarks or registered trademarks of Glory Star Group Limited. All other trademarks are the property of their respective owners.